STEN_20101_EN_0420 // STENI AS reserves the right to change product composition and specifications without prior notice. STENI AS accepts no liability for printing errors.

PRODUCT DESCRIPTION



STENI Colour

AREA OF USE

STENI Colour is a robust façade panel designed to be used as exterior ventilated cladding. It is suitable for all types of structures, and also for use as interior cladding. STENI Colour is particularly well-suited for areas where there is a lot of moisture.

ORIGIN

STENI Colour is manufactured by STENI AS in Larvik, Norway. STENI AS has developed and manufactured unique façade panels since 1965.

COMPOSITION

STENI Colour is a fibre-glass reinforced cured stone-composite panel with a core of crushed natural stone.

SURFACES

STENI Colour has a smooth surface (front) of electron beam cured acrylic with up to a 15-year colour fastness warranty. Choose from many standard colours. On request, STENI Colour can also be delivered in custom colours following the NCS Colour System or RAL. Standard gloss levels are matt (**M**), half matt (**HM**) or high gloss (**HG**). STENI Colour is a white panel dyed throughout. The edges of the panel are untreated, but can be delivered treated on request. The back of the panel is untreated.

FORMAT

STENI Colour is available in a thickness of 6 mm. Production width is 1,195 mm. Standard widths are 295, 395, 595, 795, 895 and 1,195 mm. Panels are manufactured to maximum length of 3,495 mm. Standard lengths are 850 to 3,495 mm.

UNIQUE PROPERTIES

STENI Colour is a highly resistant material that maintains its technical properties under extreme climatic conditions. These panels have excellent resistance against a variety of chemicals. Unique properties include:

- ✓ Minimalist and exclusive design
- ✓ High durability with up to a 60-year functional warranty
- ✓ Elastic and bendable
- ✓ Robust with high impact resistance
- ✓ Water impermeable and stable in humid and cold climates
- ✓ Easily washable surface that can withstand high-pressure washers up to 100 bar
- ✓ Flame-retardant, surface fire class rating: B-s1,d0

ENVIRONMENT

STENI Colour has an environmental product declaration (EPD), which is registered with EPD-Norway, IBU and ECO Platform. This product is classified by ECOproduct and Byggvarubedömningen. At STENI AS, we manufacture our products in Norway, using green energy from hydropower plants. LCC (Life Cycle Cost) is among the best on the market.